## R6-300 High-Pressure Polyamide Hose Assembly with Anti-Whip Cable Restraint



## **Product Description**

Corroflex® R6-300 Polyamide rubber high pressure hoses are manufactured in Germany according to EN ISO 14113 and supplied ready to use with 1/4" NPT female thread both ends. Suitable for use with technical gases up to and including level 4.5 purity. (\*Not suitable for Oxygen, Helium or Acetylene)

## Features & Benefits

- Manufactured in Germany according to EN ISO 14113.
- Fully assembled anti-whip cable restraint with anti-kink spring fitted both ends.
- Cleaned and suitable for technical gases up to 4.5 purity, free oil and grease.
- Excellent flexibility along with resistance to abrasion and UV.
- Suitable for many different gases according to ISO 11411.
- Test Certificate According to Directive 2014/68/EU available upon request.
- Max operating pressure 450 Bar.
- Manufactured from polyamide inner tube with high tensile carbon steel brass plated braided wire
   & polyurethane pricked cover.
- Temperature Range -40°C 96 °C







Manufactured to EN ISO 14113

Heavy Duty Anti-Whip Restraint Suitable for gases up to 4.5 purity
Free from oil & grease.

	Typical Industrial Gas Applications					
Part Number	Oxidisers*	Inert*	Flammable*	Corrosive	Specialist	Other
CH0600-6R	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>/</b>	<b>/</b>	Contact Sales
CHI000-6R	<b>✓</b>	<b>/</b>	<b>✓</b>	<b>✓</b>	<b>/</b>	Contact Sales
CHI500-6R	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>/</b>	Contact Sales
CH2000-6R	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>V</b>	<b>\</b>	Contact Sales
CH3000-6R	<b>✓</b>	<b>✓</b>	<b>✓</b>			Contact Sales
CH4000-6R	<b>✓</b>	<b>/</b>	<b>✓</b>	<b>/</b>		Contact Sales
CH5000-6R	<b>✓</b>	<b>/</b>	<b>✓</b>		<b>/</b>	Contact Sales

## R6-300 TECHNICAL DATA



	Hose Connections	2 x I/4" NPT Female		
Dimension	Nominal Bore (Metric)	6		
	ID (mm)	6.40		
	AD / OD (mm)	11.70		
Max. Pressure	Working Pressure (bar)	300		
	Test Pressure (bar)	450		
	Burst Pressure (bar)	1300		
Weight per meter (Kg)	0.16			
Bending Radius (mm)	45			
ēr	Inner Tube	Polyamide		
Corrugation / meter	Reinforcement	High tensile brass plated carbon steel		
rrugati	Cover	Polyurethane		
ŭ	End Fittings	Zinc Finished Steel		



Your local distributor:



- NOX HOSES (GLOBAL) LTD
  OLYMPIC HOUSE, COLLETT, SOUTHMEAD
  PARK, DIDCOT, OXII 7WB
- +44 (0)1235 515100
- SALES@INOXHOSES.GLOBAL
- M INOXHOSES.GLOBAL

