



# INVERTER TIG

AC/DC HF

**TT 165<sup>EVO</sup> AC/DC**  
5T3.165.302

**TT 205<sup>EVO</sup> AC/DC**  
5T3.205.302



			X %								
			40%		60%		100%				
			DC	AC	DC	AC	DC	AC			
TT 165 <sup>EVO</sup> AC/DC	1x230	5 - 165	-	-	165 A	165 A	140 A	130 A	50	13.8	270x600x450
TT 205 <sup>EVO</sup> AC/DC			5 - 200	200 A	200 A	180 A	175 A	155 A		145 A	

**TT 165<sup>EVO</sup> AC/DC** 5T3.165.302

CONFIGURAZIONE BASE DELLA MACCHINA  
• Macchina fornita senza accessori • Imballo in cartone.

**TT 205<sup>EVO</sup> AC/DC** 5T3.205.302

FACTORY CONFIGURATION  
• Accessories not included • Carton Box

## ACCESSORI OPZIONALI - OPTIONAL ACCESSORIES

	CODE	DESCRIZIONE	DESCRIPTION
	049.600.055	Cavo con morsetto di massa 25 mm <sup>2</sup> - dinse 50 mm <sup>2</sup> - 3 m	Cable with ground clamp 25 mm <sup>2</sup> - dinse 50 mm <sup>2</sup> - 3 m
	049.600.056	○ Cavo con morsetto di massa 35 mm <sup>2</sup> - dinse 50 mm <sup>2</sup> - 3 m	Cable with ground clamp 35 mm <sup>2</sup> - dinse 50 mm <sup>2</sup> - 3 m
	049.602.004	Cavo con morsetto di massa a pinza 50 mm <sup>2</sup> - dinse 50 mm <sup>2</sup> - 4 m	Cable with ground clamp 50 mm <sup>2</sup> - dinse 50 mm <sup>2</sup> - 4 m
	580.000.402	○ Riduttore a 2 manometri + riduzione CO <sub>2</sub> /Argon	Reducer two gauges + reduction CO <sub>2</sub> /Argon
	580.690.005	Carrello C 9 300mm con porta bobina	C 9 Trolley 300mm spool support
	580.690.012	○ Carrello C 11s	C 11s Trolley
	421.300.014	Kit montaggio parete frontale trolley C11s *	Front panel for C11s (assembly kit)*
	421.100.009	Comando a distanza manuale PRO - L= 5 m - conn. 7 pin	PRO Manual remote control - L= 5 m - 7 pin connector
	421.101.007	Comando a distanza pedale PRO - Conn. 7 pin	PRO Foot remote control - 7 pin connector
	421.200.103	Prolunga comando a distanza pedale L= 5 m - conn. 7 pin	Extension foot remote control L=5m - 7 pin conn.
	421.200.104	Prolunga comando a distanza pedale L= 10 m - conn. 7 pin	Extension foot remote control L=10m - 7 pin conn.
	421.200.105	Prolunga comando a distanza pedale L= 20 m - conn. 7 pin	Extension foot remote control L=20m - 7 pin conn.

## AIR KIT

	043.600.230	Torcia TT 17 - 4 m - connettore 7 pin	Torch TT 17 - 4 m - 7 pin connector
	043.600.231	Torcia TT 17 - 8 m - connettore 7 pin	Torch TT 17 - 8 m - 7 pin connector
	043.600.242	Torcia TT 17 PRO - 4 m - connettore 7 pin	Torch TT 17 PRO - 4 m - 7 pin connector
	043.600.243	Torcia TT 17 PRO - 8 m - connettore 7 pin	Torch TT 17 PRO - 8 m - 7 pin connector
	043.601.236	○ Torcia TT 26 - 4 m - connettore 5 pin	Torch TT 26 - 4 m - 5 pin connector
	043.601.239	Torcia TT 26 - 8 m - connettore 5 pin	Torch TT 26 - 8 m - 5 pin connector
	043.601.244	Torcia TT 26 PRO - 4 m - connettore 5 pin	Torch TT 26 PRO - 4 m - 5 pin connector
	043.601.245	Torcia TT 26 PRO - 8 m - connettore 5 pin	Torch TT 26 PRO - 8 m - 5 pin connector

## KIT H<sub>2</sub>O

	580.522.053	○ Unità di raffreddamento	Water cooling unit
	920.500.042	○ Fluido refrigerante 5l per Unità	Cooling fluid 5l
	920.500.043	Fluido refrigerante 10l per Unità	Cooling fluid 10l
	043.601.250	Torcia TT 20 - 4 m - dinse 50 mm <sup>2</sup> - connettore 5 pin	Torch TT 20 - 4 m - dinse 50 mm <sup>2</sup> - 5 pin connector
	043.601.251	Torcia TT 20 - 8 m - dinse 50 mm <sup>2</sup> - connettore 5 pin	Torch TT 20 - 8 m - dinse 50 mm <sup>2</sup> - 5 pin connector
	043.601.248	○ Torcia TT 20 PRO - 4 m - dinse 50 mm <sup>2</sup> - connettore 5 pin con adattatore 5/7 pin	Torch TT 20 PRO - 4 m - dinse 50 mm <sup>2</sup> - 5 pin connector with 5/7 pin adaptor
	043.601.249	Torcia TT 20 PRO - 8 m - dinse 50 mm <sup>2</sup> - connettore 5 pin con con adattatore 5/7 pin	Torch TT 20 PRO - 8 m - dinse 50 mm <sup>2</sup> - 5 pin connector with 5/7 pin adaptor

## ACCESSORI MMA - MMA ACCESSORIES

	489.603.411	Kit cavi completo 25 mm <sup>2</sup> - dinse 50 mm <sup>2</sup> - L=3+2	Cables set complete 25 mm <sup>2</sup> - dinse 50 mm <sup>2</sup> - L=3+2
--	-------------	-------------------------------------------------------------------------	---------------------------------------------------------------------------

\* Solo per macchine raffreddate ad aria o senza toolbox  
Only for air cooled machine without toolbox

○ FIMER recommended configuration  
● Accessories included / Factory configuration