

# **MW 300 S-GRE**

ENGINE DRIVEN WELDER/GENERATOR / DELIVERS 300 A OF DC WELD OUTPUT / THREE-PHASE AND SINGLE-PHASE AUXILIARY POWER AVAILABLE / DIESEL ENGINE 3000 RPM

#### **Gen Set Features**

#### Welding Processes: SMAW (stick) / TIG

- + DAS, auto engine protection shutdown system with warning lights in case of:
- battery charger failure
- low fuel level
- low oil pressure
- + Automatic idle device when no load is connected
- + 12V built-in battery with electric start
- + Engine hourmeter
- + Fuel level gauge
- + 1 x 16A, 400 V 50 Hz three-phase EEC socket

- + 1 x 32A, 230 V 50 Hz single-phase EEC socket protected by circuit breaker
- + 1 x 48 V 50 Hz single-phase outlet (safety low voltage)
- + Earth Leakage Circuit Breaker (ELCB)
- + Voltmeter
- + Remote control socket
- + ARC FORCE CONTROL switch
- + Central lifting eye
- Two-wheels site tow undercarriage (GRT2W)

### **Gen Set Options** (available as factory

- + LIFT START TIG facility
- + CC/CV control for MIG welding
- + Spark arrester muffler
- + Versions with different voltages

### Accessories on Request

options)

- + Remote control unit with 20m cable and plug
- + Parallel Welding Box with ammeter and voltmeter (P-BOX)
- + Welding cables Ø 35 mm<sup>2</sup> (5+3 m) with accessories
- + Reverse polarity switch kit
- + Trolley: two-wheels and handles
- + Skid base for use directly on the ground
- + MIG wire feeder

### **Noise Level**

+ Lwa 99

(74 dB at 7m) 300 A - 32 V

### **DC** Welding

+ Duty Cycle @ 60% + Stepless current control

+ Duty Cycle @ 35%

- 250 A 30 V 30 A ÷ 300 A
- + Open Circuit Voltage
  - 70 V 6 mm

### **AC** Generator 50 Hz

- + Type Gen Set asynchronous self-excited and self-protected
- + Three-phase power
- + Single-phase power + Single-phase power

+ Starting system

+ Max welding rod

7 kVA - 230 V 5 kVA - 48 V

electric

38 I

3,3 l/h

- 8 kVA 400 V
- + Power Factor 8,0

#### **Diesel Engine** 3000 rpm

- + Type Ruggerini RD210 2 cyl. 20 HP (14,7 kWm) - 954 cm<sup>3</sup>
- + Fuel diesel + Cooling system air
- + Fuel tank capacity + Fuel consumption @ 75%

### **Other Features**

- F + Insulation Class
- IP 23 + Mechanical Protection
- + Dimensions (L x W x H)
- 1300 x 620 x 810 mm (trailer not included)
- + Dry Weight
- 325 kg

## **MW 300 S-GRE**



