Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) Printed 07.08.2016 revision 07.06.2016 (GB) Version 1.0 Temporary Line Marker(GB)

# ! SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Name of product

Temporary Line Marker(GB) Aerosol

**1.2. Relevant identified uses of the substance or mixture and uses advised against Recommended intended purpose(s)** Technical Aerosols

1.3. Details of the supplier of the safety data sheet

Supplier

AES Industrial Supplies Ltd Olympic House, Collett, Southmead Park Didcot, OX11 7WB United Kingdom Phone +44(0) 1235 510717 Email: orders@aes-sales.com Website: http://www.1stopweldingshop.com

## 1.4. Emergency telephone number

Emergency advice

+44 (0) 1235 510717

# **! SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture ! Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]

Hazard classes and categories	d Hazard	Hazard Statements	Classification procedure
Aerosol 1 Aquatic Chronic 2		H222, H229 H411	
Hazard Statement H222 H229	Extremely fla	immable aerosol. container: May burst if	heated.
H411	Toxic to aquatic life with long lasting effects.		

# 2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]



# ! Signal word

Danger

# **Hazard Statements**

Indeal a statemente	
H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H411	Toxic to aquatic life with long lasting effects.

# **Precautionary Statements**

P102 Keep out of reach of children.

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P273	Avoid release to the environment.
P410 + P412	Protect from sunlight. Do no expose to temperatures exceeding 50°C/122°F.
P501	Dispose of contents/container to hazardous or special waste collection point.

## 2.3. Other hazards

Product has an anesthetic effect.

### Information pertaining to special dangers for human and environment In extensive use, formation of flammable / explosive vapour-air mixture is possible.

! Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

# **! SECTION 3: Composition/ information on ingredients**

### Description

Line Marker based on synthetic resin binder, solvent and pigments.

### 3.2. Mixtures

# ! Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
25587-80-8	N/A	Polyamide resin	10<12	No Classified
N/A	N/A	Pigment	12< 18	No Classified
115-10-6	204-065-8	Dimethyl ether	30< 34	Flam. Gas 1, H220 / Press. Gas, H280
471-34-1	207-439-9	Calcium carbonate	20 < 24	No Classfied
64-17-5	200-578-6	Ethyl Alcohol	18< 20	Flam. Liq. 2; Eye Dam., 2A; H225; H319;
1317-80-2	257-372-4	Titanium Dioxide	9< 10	No Classified

# **SECTION 4: First aid measures**

# 4.1. Description of first aid measures

# General information

Remove contaminated soaked clothing immediately.

### In case of inhalation

Remove the casualty into fresh air and keep him immobile. In the event of symptoms refer for medical treatment.

### In case of skin contact

In case of contact with skin wash off with soap and water. Consult a doctor if skin irritation persists.

## In case of eye contact

In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice.

# In case of ingestion

Do not induce vomiting. Medical treatment.

# 4.2. Most important symptoms and effects, both acute and delayed

No information available.

**4.3. Indication of any immediate medical attention and special treatment needed** No information available.

# **! SECTION 5: Firefighting measures**

# 5.1. Extinguishing media

! Suitable extinguishing media Carbon dioxide Dry sand

Unsuitable extinguishing media water

# 5.2. Special hazards arising from the substance or mixture

May lead to formation of explosive/easily ignitable vapour air mixtures. Danger of bursting

# 5.3. Advice for firefighters

# Special protective equipment for fire-fighters

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

# ! Additional information

Vapours are heavier than air and will spread on the ground.

Cool endangered containers with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

# **! SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

! For non-emergency personnel

Ensure adequate ventilation.

Use personal protective clothing.

Keep away sources of ignition.

Use breathing apparatus if exposed to vapours/dust/aerosol.

Pay attention to extension of gas especially at ground (heavier than air) and in direction of the wind.

### 6.2. Environmental precautions

Inform pollution control authorities if product gets into the sewerage systems or open waters. Do not discharge into the drains or bodies of water..

### 6.3. Methods and material for containment and cleaning up

Take up with absorbent material. After taking up the material dispose according to regulation.

# 6.4. Reference to other sections

Safe handling: see section 7 Disposal: see section 13 Personal protection equipment: see section 8

# **! SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

### ! Advice on safe handling

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace. Take measures against electrostatically charging.

### **General protective measures**

Avoid contact with eyes and skin Do not inhale gases/vapours/aerosols.

#### ! Hygiene measures

At work do not eat, drink, smoke or take drugs. Wash hands before breaks and after work.

# ! Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking Do not spray on a naked flame or any incandescent material. Pressurized container. Do not pierce or burn even after use. Vapours can form an explosive mixture with air. Avoid effect of heat. Use explosion-proof equipment / fittings and non-sparking tools.

### 7.2. Conditions for safe storage, including any incompatibilities

# Requirements for storage rooms and vessels

Keep in closed original container.

Adhere to administrative regulations relating to storage of compressed gas cylinders / containers.

# Further information on storage conditions

# Protect from direct solar radiation.

Storage temperature may not exceed 50°C (=122°F). Store container at cool and aired place.

# 7.3. Specific end use(s)

! Recommendation(s) for intended use

See section 1.2

# **! SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

### ! Ingredients with occupational exposure limits to be monitored

CAS No	Name	Code	[mg/m3]	[ppm]	Remark
115-10-6	Dimethyl ether	8 hours	1920	N/A	IOELV
64-17-5	Ethyl Alcohol	8 hours	1920	1000	IOELV

## Indicative occupational exposure limit values (91/322/EEC, 2000/39/EC, 2006/15/EC or 2009/161/EU)

CAS No	Name	Code	[mg/m3]	[ppm]	Remark
115-10-6	Dimethyl ether	8 hours	1920	N/A	skin,eye
64-17-5	Ethyl Alcohol	8 hours	950	500	Skin, Eye

### Additional advice

The statutory local and national regulations have to be observed.

### 8.2. Exposure controls

## **Respiratory protection**

If ventilation insufficient, wear respiratory protection.

Short-term: filter apparatus, filter AX, otherwise environment-independent breathing apparatus.

### Hand protection

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: butyl rubber, 0,7mm; 480min

# ! Eye protection

tightly fitting goggles

# Other protection measures protective clothing

### Appropriate engineering controls

Sufficient ventilation and exhaustion.

# **! SECTION 9: Physical and chemical properties**

<b>Appearance</b> aerosol		<b>olour</b> ilver-grey		Odour solvent-	like
Odour threshold not determined					
mportant health, safety and	d environmental i	nformation			
	Value	Temperature	at	Method	Remark
pH value	not determined				
boiling point	not applicable				
Melting point / Freezing point	not determined				
Flash point	not applicable				Aerosol
Vapourisation rate	not determined				
Flammable (solid)	not determined				
Flammability (gas)	not determined				
gnition temperature	not determined				
Self ignition temperature	not determined				
Lower explosion limit	not determined				
Upper explosion limit	not determined				
Vapour pressure	not determined				
Relative density	not determined				
Vapour density	not determined				
Solubility in water	not determined				
Solubility/other	not determined				
Partition coefficient n- octanol/water (log P O/W)	not determined				
Decomposition temperature	not determined				
Viscosity dynamic					not determined
Viscosity kinematic					not determined

No information available.

### Explosive properties

The product is considered non-explosive ; nevertheless explosive vapour/air mixtures can be generated .

# 9.2. Other information

No information available.

# **! SECTION 10: Stability and reactivity**

# 10.1. Reactivity

no

# 10.2. Chemical stability

No information available.

# 10.3. Possibility of hazardous reactions

Possibility of hazardous reactions

## 10.4. Conditions to avoid

Keep away from heat. Formation of explosive gas/air mixtures.

# 10.5. Incompatible materials

No information available.

# 10.6. Hazardous decomposition products

# **Thermal decomposition**

Remark No decomposition if used as directed.

# **! SECTION 11: Toxicological information**

# 11.1. Information on toxicological effects

# Acute toxicity/Irritability/Sensitization

	Value/Validation	Species	Method	Remark
LD50 acute oral	> 2000 mg/kg	rat		Information concerns to main component.
LD50 acute dermal	1100 mg/kg			Xylene
LC50 acute inhalation	> 5 mg/l (4 h)	rat		Aluminium
Irritability skin	irritant			
Irritability eye	irritant			

# ! Experiences made from practice

Often and long skin contact may cause degreasing and desiccation of the skin which may caus skin irritation. Irritates respiratory tract. Irritates eyes and skin.

### ! Additional information

The product is to be handled with the caution usual with chemicals. Other hazardous properties may not be excluded.

# **! SECTION 12: Ecological information**

# 12.1. Toxicity

No information available.

## 12.2. Persistence and degradability

No information available.

### 12.3. Bioaccumulative potential

No information available.

### 12.4. Mobility in soil

No information available.

### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

## 12.6. Other adverse effects

### ! General regulation

! Waste code No.

08 01 11\*

Toxic to aquatic life with long lasting effects. Do not allow uncontrolled leakage of product into the environment. Product is not allowed to be discharged into aquatic environment.

# **! SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

### Name of waste

waste paint and varnish containing organic solvents or other dangerous substances

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 2008/98/EC on hazardous waste.

### ! Recommendations for the product

Remove in accordance with local official regulations.

### **Recommendations for packaging**

Dispose of according to the local waste regulations.

### **General information**

For proper waste disposal a complete emptying of the tin is necessary.

# **SECTION 14: Transport information**

	ADR/RID	IMDG	IATA-DGR
14.1. UN number	1950	1950	1950
14.2. UN proper shipping name	AEROSOLS	AEROSOLS (ZINC POWDER)	Aerosols, flammable
14.3. Transport hazard class(es)	2.1	2.1	2.1
14.4. Packing group	-	-	-
14.5. Environmental hazards	Yes	Yes	Yes

## 14.6. Special precautions for user

No information available.

# 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code not applicable

### Land and inland navigation transport ADR/RID

Hazard label(s) 2.1 tunnel restriction code D Classification code 5F transport in "limited quantities" according to 3.4 ADR is possible

# Marine transport IMDG

MARINE POLLUTANT Transport as limited quantities according to 3.4 IMDG Code is possible.

## Transport/further information

24h EMERGENCY CONTACT (TRANSPORT) +49(0)178 433 7434 (Consultank Lutz Harder GmbH)

# **! SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC standard VOC content VOC value

0 % NONE

### 15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

# **SECTION 16: Other information**

## **Recommended uses and restrictions**

National and local regulations concerning chemicals shall be observed. For industrial use only.

### **Further information**

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product. Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EU-directives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 8.0

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H228 Flammable solid.
- H261 In contact with water releases flammable gases.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H336 May cause drowsiness or dizziness.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.

#### Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such infomation is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.