

SINGLEPHASE INDUSTRIAL VACUUMS

**PERFORMANCE ON
VACUUM SOLUTIONS
SINCE 1972**



**POWER
RELIABILITY
SAFETY**

POWER & RELIABILITY


ADVANTAGES

MAXIMUM POWER 3,9 KW

BY-PASS COOLING SYSTEM

INDEPENDENT SWITCHES

Suitable for every need, the by-pass motors installed by Depureco are powerful and reliable. Thanks to their independent cooling system they can work in the most demanding conditions. Dust, swarf, oil and every type of liquid are quickly vacuumed, even with several meters long hoses. The three-motors version is the most powerful in its category and can reach outstanding performances.



UP TO 3 MOTORS TO REACH THE UTMOST PERFORMANCES



THE RIGHT FILTER FOR EVERY CIRCUMSTANCE

POCKET FILTER



STANDARD M CLASS FILTER

FINE DUST, GRANULES, SOLID AND DRY SWARF



M CLASS ANTISTATIC FILTER

FINE DUST, GRANULES, SWARF AND SOLID MATERIALS THAT TEND TO BECOME ELECTROSTATICALLY CHARGED. STANDARD ON THE MODELS IN THE ATEX RANGE.



NOMEX FILTER

DUST AND SOLID MATERIALS WITH TEMPERATURES UP TO 250°C.



M CLASS TEFLON FILTER

FINE DUST, GRANULES, WET OR DUMP SWARF AND SOLID MATERIALS. ESPECIALLY SUITABLE FOR STICKY DUST.



M CLASS PTFE FILTER

VERY FINE AND STICKY DUST, HYGROSCOPIC AND WET MATERIALS. FOOD CERTIFIED



M CLASS ANTISTATIC PTFE FILTER

HYGROSCOPIC MATERIALS THAT TEND TO BECOME ELECTROSTATICALLY CHARGED. STANDARD ON MODELS IN THE ATEX RANGE. FOOD CERTIFIED.

FILTER FOR THE JETCLEAN SYSTEM




- _____ M CLASS - FILTRATION EFFICIENCY 1 μ (EN60335269)
- _____ FILTER SURFACE UP TO 35.000 cm²
- _____ JETCLEAN® FILTER CLEANING SYSTEM
- _____ ANTISTATIC POLYESTER ALUMINATED FILTER
- _____ ESPECIALLY SUITED FOR DRY, FINE AND VERY FINE DUST



CLASS H14 EN - 1822
EFFICIENCY 99,995% VERY FINE, DANGEROUS DUST WITH GRANULOMETRY <1 μ

ABSOLUTE FILTER



THE MATERIAL ENTERS THE CHAMBER FROM THE SUCTION INLET (1) AND THANKS TO THE CYCLONE (2) IT LOSES SPEED, SETTLING INSIDE THE VACUUM'S BIN (3). THIS WAY 90% OF THE MATERIAL IS CLEARED, GRANTING A LONGER LIFE FOR THE FILTER.

THE CYCLONE




STANDARD M CLASS FILTER

THE M CLASS FILTER HAS A FILTRATION EFFICIENCY OF 1 μ , ALLOWING TO VACUUM EVEN FINER DUST IN COMPLETE SAFETY



THE TRICK IS CLEANING THE FILTER!



JETCLEAN® SYSTEM

IT CLEANS THE FILTER WITHOUT STOPPING THE VACUUMING
INCREASED CLEANING EFFICIENCY UP TO 30% HIGHER
IDEAL FOR FINE AND DIFFICULT DUST

MANUAL FILTER SHAKER

IDEAL FOR DRY AND HUMID DUST
EXCELLENT TO REMOVE SWARF AND SOLID MATERIALS FROM THE FILTER
PRACTICAL AND CHEAP SYSTEM



VACUUM CLEANERS WITH JETCLEAN® SYSTEM

COMPACT

DURABLE

SAFE

- Semi-Automatic filter cleaning system
- All the filters are certified M Class
- Up to 3 motors
- Powerful, Compact and Durable
- Ideal for fine and dry dust
- Practical Detachable Bin
- Up To 100 Lt Capacity
- Available With Longopac®



	XM 20 JETCLEAN	XM 35 JETCLEAN	XM 35 JETCLEAN LP	M 65 JETCLEAN	M 100 JETCLEAN LP
MOTORS	2	2	2	3	3
POWER	kW-HP 2,6 - 3,5	kW-HP 2,6 - 3,5	kW-HP 2,6 - 3,5	kW-HP 3,9 - 5,2	kW-HP 3,9 - 5,2
VOLTAGE FREQUENCY	V Hz 230 / 50-60	V Hz 230 / 50-60	V Hz 230 / 50-60	V Hz 230 / 50-60	V Hz 230 / 50-60
MAXIMUM VACUUM	mBar 250	mBar 250	mBar 250	mBar 250	mBar 250
MAXIMUM AIR FLOW	m³/h 380	m³/h 380	m³/h 380	m³/h 570	m³/h 570
INLET	Ø mm 50	Ø mm 50	Ø mm 50	Ø mm 50	Ø mm 50
FILTER SURFACE	cm² 35.000	cm² 35.000	cm² 35.000	cm² 35.000	cm² 35.000
CAPACITY	Lt 20	Lt 45	LONGOPAC®	Lt 65/100	LONGOPAC®



CONICAL FILTER CARTRIDGE

WITH STANDARD M CLASS FILTER AND SEMI-AUTOMATIC JETCLEAN® FILTER CLEANING SYSTEM



ABSOLUTE FILTER

AVAILABLE FOR THE WHOLE RANGE



SLIDING DAMPER

AVAILABLE FOR ALL MODELS



UP TO THREE YEARS WARRANTY

VACUUM CLEANERS WITH POCKET FILTER

POWERFUL

VERSATILE

RELIABLE

- Manual Filter Shaker
- All the Filters are certified M Class
- Up to 3 motors
- Sturdy, Safe, suitable for every need
- Ideal for Dust, Granules and Swarf
- Practical detachable Bin
- Up To 100 Lt Capacity
- Available With Longopac®



MINIBULL

M 65 / 100

BULL UNO 2 M / 3M

		MINIBULL		M 65 / 100		BULL UNO 2 M / 3M
MOTORS		2		3		2 / 3
POWER	kW-HP	2,6 - 3,5		kW-HP	3,9 - 5,2	kW-HP 2,6 - 3,5 / 3,9 - 5,2
VOLTAGE FREQUENCY	V Hz	230 / 50 - 60		V Hz	230 / 50 - 60	V Hz 230 / 50 - 60
MAXIMUM VACUUM	mBar	250		mBar	250	mBar 250
MAXIMUM AIR FLOW	m³/h	380		m³/h	570	m³/h 380 / 570
INLET	Ø mm	70		Ø mm	70	Ø mm 80
FILTER SURFACE	cm²	15.000		cm²	24.000 / 38.000	cm² 24.000 / 38.000
CAPACITY	Lt	45		Lt	65 / 100	Lt 65 / 100



**STANDARD M CLASS POCKET FILTER
SUITABLE FOR EVERY NEED**



**ABSOLUTE
FILTER**
AVAILABLE FOR THE
WHOLE RANGE



SP SYSTEM

**AUTOMATIC REVERSE AIR JET
FILTER CLEANING. AVAILABLE
ON DEMAND.**



**UP TO THREE YEARS
WARRANTY**

WD VACUUM CLEANER FOR LIQUIDS

WD 132 | WD 132 P | WD 133

MOTORS		2	2	3
POWER	kW-HP	2,6-3,5	2,6-3,5	3,9-5,2
VOLTAGE FREQUENCY	V Hz	230/50-60	230/50-60	230/50-60
MAXIMUM VACUUM	mBar	250	250	250
MAXIMUM AIR FLOW	m³/h	380	380	570
INLET	Ø mm	70	70	70
CAPACITY	Lt	130	130	130
DISCHARGE SYSTEM		discharge by gravity	automatic discharge by pump	discharge by gravity



FLOATING SYSTEM



STANDARD FILTER FOR LIQUIDS



STANDARD FILTER FOR DUST



BATTERY POWERED VACUUM CLEANER

BULL 24 | FOX 24

MOTORS		3	3
POWER	kW-HP	1,5/2	1,5/2
VOLTAGE FREQUENCY	V	24	24
MAXIMUM VACUUM	mBar	240	240
MAXIMUM AIR FLOW	m³/h	350	350
INLET	Ø mm	80	80
BATTERY	N°	2	4
UPTIME	h	1	2



ACCESSORIES

CONVENIENT SOLUTIONS TO HELP YOU WITH YOUR WORK



FIXED VACUUMING TOOL



BIN EMPTYING KIT



LONGOPAC® SEPARATOR



WET & DRY SEPARATOR



TILTABLE 580 LT SEPARATOR

THE RIGHT ACCESSORY FOR EVERY NEED



DOUBLE BEND TUBE FOR FLOOR BRUSH



FLOOR BRUSH WITH BRISTLES



FLOOR SQUEEGEE WITH RUBBER STRIPS



SCRAPING PIPE



PIPE WITH HANDLE



ANTISTATIC RUBBER CONIC SECTION



OIL PROOF CONIC SECTION



SILICONE CONIC SECTION



ANTISTATIC SWEEPER NOZZLE



ANTISTATIC BRUSH WITH BRASS BRISTLES



ANTISTATIC RUBBER BRUSH WITH BRASS BRISTLES



PVC ROUND BRUSH



ANTISTATIC BENT RUBBER CONE



PIPE CLEANING BRUSH



ANTISTATIC FLAT PIPE

FLEXIBLE HOSES FOR ALL MATERIALS



BLACK EVAFLEX HOSE



BLACK EVAFLEX ELECTROCONDUCTIVE HOSE




POLYURETHANE FLEXIBLE HOSE



REINFORCED ABRASIVE PROOF POLYURETHANE FLEXIBLE HOSE



ANTISTATIC POLYURETHANE FLEXIBLE HOSE



DEPURECO INDUSTRIAL VACUUMS SRL

Corso Venezia, 32 - 10088 Volpiano (TO) Italia

Tel. +39 011 98.59.117 Fax. +39 011 98.59.326

C.F. e P.I. 02258610357

depureco@depureco.com www.depureco.com

 **DEPURECO**[®]
INDUSTRIAL VACUUMS